



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

FIRST300B / FIRST410B, Comp. A

UFI: DFYH-D8RR-8G0W-KRHW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: Scell-it

Street: 28 rue Paul Dubrule Place: F-59810 Lesquin

Telephone: +33(0) 320 329 818 Telefax: +33(0) 320 329 817

e-mail: technique@scellit.com
e-mail (Contact person): qualite@scellit.com
Internet: www.scellit.com

1.4. Emergency telephone Guy's St thomas' Poisons Unit, London: +44 870 243 2241

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Sens. 1; H317 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Tetramethylene dimethacrylate;

Methacrylic acid, monoester with propane-1,2-diol;

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl]

(4-methylphenyl)amino]

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 2 of 16

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container to an approved waste disposal plant in accordance with

local/national regulation.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulat	ion)			
2082-81-7	Tetramethylene dimethacrylate			5 - < 15 %	
	218-218-1		01-2119967415-30		
	Skin Sens. 1B; H317				
25013-15-4	Vinyltoluene			1 - < 6 %	
	246-562-2		01-2119622074-50		
	Flam. Liq. 3, Acute Tox. 4, Skin H332 H315 H319 H400 H411	Irrit. 2, Eye Irrit. 2, Aquatic A	cute 1, Aquatic Chronic 2; H226		
27813-02-1	Methacrylic acid, monoester wit	h propane-1,2-diol		< 2,5 %	
	248-666-3		01-2119490226-37		
	Eye Irrit. 2, Skin Sens. 1; H319	H317	•		
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate				
	229-934-9		01-2119451093-47		
	Repr. 2, Aquatic Chronic 3; H361d H412				
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]				
	911-490-9		01-2119979579-10		
	Acute Tox. 4, Skin Irrit. 2, Eye DH412	Dam. 1, Skin Sens. 1, Aquatic	Chronic 3; H302 H315 H318 H317		
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol			< 0,5 %	
	254-075-1		01-2119980937-17		
	Acute Tox. 2, Eye Irrit. 2, Aquat	ic Chronic 3; H300 H319 H41	2		
130-15-4	1,4-naphthoquinone			< 0,05 %	
	204-977-6		01-2120760462-57		
	Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H330 H301 H314 H318 H317 H335 H400 H410				

Full text of H and EUH statements: see section 16.



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 3 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Cond	c. Limits, M-factors and ATE	
2082-81-7	218-218-1	Tetramethylene dimethacrylate	5 - < 15 %
	dermal: LD5	0 = > 3000 mg/kg; oral: LD50 = 10066 mg/kg	
25013-15-4	246-562-2	Vinyltoluene	1 - < 6 %
	inhalation: A 4585 mg/kg	TE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 =	
27813-02-1	248-666-3	Methacrylic acid, monoester with propane-1,2-diol	< 2,5 %
	dermal: LD5	0 = > 5000 mg/kg; oral: LD50 = > 2000 mg/kg	
6846-50-0	229-934-9	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate	< 0,5 %
	dermal: LD5	0 = 18900 mg/kg; oral: LD50 = 3200 mg/kg	
-	911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	< 0,5 %
	dermal: LD5	0 = > 2000 mg/kg; oral: LD50 = 619 mg/kg	
38668-48-3	254-075-1	1,1'-(p-Tolylimino)dipropan-2-ol	< 0,5 %
	dermal: LD5	0 = > 2000 mg/kg; oral: LD50 = > 25 - < 200 mg/kg	
130-15-4	204-977-6	1,4-naphthoquinone	< 0,05 %
		TE = 0,5 mg/l (vapours); inhalation: LC50 = 0,046 mg/l (dusts or mists); oral: LD50 M acute; H400: M=10 10: M=1	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eves

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam
Extinguishing powder
Water spray jet
Carbon dioxide (CO2)





according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 4 of 16

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic Carbon monoxide

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protective equipment as required. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not use for products which come into contact with the food stuffs.





according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 5 of 16

Further information on storage conditions

storage temperature: 5 - 25°C

7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 6 of 16

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
2082-81-7	Tetramethylene dimethacrylate			
Worker DNEL	., long-term	inhalation	systemic	14,5 mg/m³
Worker DNEL	, long-term	dermal	systemic	4,2 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	systemic	4,3 mg/m³
Consumer DN	IEL, long-term	dermal	systemic	2,5 mg/kg bw/day
Consumer DN	IEL, long-term	oral	systemic	2,5 mg/kg bw/day
25013-15-4	Vinyltoluene			
Worker DNEL	., long-term	inhalation	systemic	37 mg/m³
Worker DNEL	., acute	inhalation	systemic	37 mg/m³
Worker DNEL	., long-term	inhalation	local	37 mg/m³
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
Worker DNEL	., long-term	inhalation	systemic	14,7 mg/m³
Worker DNEL	., long-term	dermal	systemic	4,2 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	systemic	8,8 mg/m³
Consumer DN	IEL, long-term	dermal	systemic	2,5 mg/kg bw/day
Consumer DN	IEL, long-term	oral	systemic	2,5 mg/kg bw/day
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate			
Worker DNEL	., long-term	dermal	systemic	5 mg/kg bw/day
Worker DNEL	, long-term	inhalation	systemic	17,62 mg/m³
Consumer DN	IEL, long-term	inhalation	systemic	4,35 mg/m³
Consumer DN	IEL, long-term	oral	systemic	5 mg/kg bw/day
Consumer DN	IEL, long-term	dermal	systemic	5 mg/kg bw/day
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisetha (4-methylphenyl)amino]	anol and Ethanol 2-[[2	2-(2-hydroxyethoxy)	ethyl]
Worker DNEL	, long-term	inhalation	systemic	9,8 mg/m³
Worker DNEL	, long-term	dermal	systemic	1,4 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	systemic	2,9 mg/m³
Consumer DN	IEL, long-term	oral	systemic	0,83 mg/kg bw/day
Consumer DN	IEL, long-term	dermal	systemic	0,83 mg/kg bw/day
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol			
Worker DNEL	, long-term	inhalation	systemic	2 mg/m³
Worker DNEL	, long-term	dermal	systemic	0,6 mg/kg bw/day
Consumer DN	IEL, long-term	oral	systemic	0,3 mg/kg bw/day
Consumer DN	IEL, long-term	dermal	systemic	0,3 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	systemic	0,4 mg/m³
130-15-4	1,4-naphthoquinone			
Worker DNEL	, long-term	inhalation	systemic	0,033 mg/m³



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 7 of 16

PNEC values

CAS No Substance	
Environmental compartment	Value
2082-81-7 Tetramethylene dimethacrylate	
Freshwater	0,043 mg/l
Marine water	0,004 mg/l
Freshwater sediment	3,12 mg/kg
Marine sediment	0,312 mg/kg
Micro-organisms in sewage treatment plants (STP)	2 mg/l
Soil	0,573 mg/kg
25013-15-4 Vinyltoluene	<u> </u>
Freshwater	0,05 mg/l
Marine water	0,002 mg/l
Freshwater sediment	0,684 mg/kg
Marine sediment	0,684 mg/kg
Soil	0,133 mg/kg
27813-02-1 Methacrylic acid, monoester with propane-1,2-c	liol
Freshwater	0,904 mg/l
Marine water	0,904 mg/l
Freshwater sediment	6,28 mg/kg
Marine sediment	6,28 mg/kg
Micro-organisms in sewage treatment plants (STP)	10 mg/l
Soil	0,727 mg/kg
6846-50-0 1-lsopropyl-2,2-dimethyltrimethylene Diisobutyr	ate
Freshwater	0,014 mg/l
Marine water	0,001 mg/l
Freshwater sediment	5,29 mg/kg
Marine sediment	0,529 mg/kg
Soil	1,05 mg/kg
Reaction mass of 2,2'-[(4-methylphenyl)imino]b (4-methylphenyl)amino]	isethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl]
Freshwater	0,048 mg/l
Marine water	0,005 mg/l
Freshwater sediment	0,12 mg/kg
Marine sediment	0,12 mg/kg
38668-48-3 1,1'-(p-Tolylimino)dipropan-2-ol	
Freshwater	0,017 mg/l
Marine water	0,0017 mg/l
Freshwater sediment	0,0783 mg/kg
Marine sediment	0,0072 mg/kg
Soil	0,005 mg/kg
130-15-4 1,4-naphthoquinone	
Freshwater	26,1 mg/l
Marine water	2,61 mg/l



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 8 of 16

Freshwater sediment	321 mg/kg
Marine sediment	32,1 mg/kg
Micro-organisms in sewage treatment plants (STP)	0,172 mg/l
Soil	49 mg/kg

Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Wear safety glasses.

Hand protection

Disposable gloves

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: > 0,2 mm

DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: solid (pasty)
Colour: light beige
Odour: characteristic
Odour threshold: No data available

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

not determined
not determined

boiling range:

Flash point: not applicable

Flammability

Solid/liquid: not determined



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 9 of 16

Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Self-ignition temperature

Solid: not determined Gas: not applicable Decomposition temperature: not determined pH-Value: not determined

Water solubility: The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 20 °C):

Relative vapour density:

not determined

1,72 g/cm³

not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties Not oxidising.

Other safety characteristics

Solid content: not determined Evaporation rate: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Response: Oxidising agent, strong

10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 11282,6 mg/kg; ATE (inhalation vapour) 265,95 mg/l; ATE (inhalation dust/mist) 36,266 mg/l



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 10 of 16

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
2082-81-7	Tetramethylene dimet	thacrylate						
	oral	LD50 mg/kg	10066	Rat				
	dermal	LD50 mg/kg	> 3000	Rabbit				
25013-15-4	Vinyltoluene							
	dermal	LD50 mg/kg	4585	Rabbit				
	inhalation vapour	_	11 mg/l					
	inhalation dust/mist	ATE	1,5 mg/l					
27813-02-1	Methacrylic acid, mon	oester with pr	ropane-1,	2-diol				
	oral	LD50 mg/kg	> 2000	Rat				
	dermal	LD50 mg/kg	> 5000	Rabbit				
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate							
	oral	LD50 mg/kg	3200	Rat				
	dermal	LD50 mg/kg	18900	Guinea pig				
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]							
	oral	LD50 mg/kg	619	Rat				
	dermal	LD50 mg/kg	> 2000	Rat				
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol							
	oral	LD50 200 mg/kg	> 25 - <	Rat				
	dermal	LD50 mg/kg	> 2000	Rat				
130-15-4	1,4-naphthoquinone							
	oral	LD50 mg/kg	124	Rat				
	inhalation vapour		0,5 mg/l					
	inhalation (4 h) dust/mist	LC50 mg/l	0,046	Rat				

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Tetramethylene dimethacrylate; Methacrylic acid, monoester with propane-1,2-diol; Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]; 1,4-naphthoquinone)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.





according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 11 of 16

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 12 of 16

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
2082-81-7	Tetramethylene dimethacrylate						
	Acute algae toxicity	ErC50 mg/l	9,79	72 h			
	Crustacea toxicity	NOEC mg/l	5,09	21 d			
25013-15-4	Vinyltoluene						
	Acute fish toxicity	LC50 mg/l	1 - 10	96 h			
	Acute algae toxicity	ErC50 mg/l	0,319	72 h			
	Acute crustacea toxicity	EC50	9,3 mg/l	48 h	Daphnia magna (Big water flea)		
27813-02-1	Methacrylic acid, monoe	ester with p	propane-1,2	2-diol			
	Acute algae toxicity	ErC50 mg/l	> 97,2	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 mg/l	> 143	48 h	Daphnia magna (Big water flea)		
	Algae toxicity	NOEC	mg/l				
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate						
	Algae toxicity	NOEC mg/l	2,25	3 d			
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]						
	Acute fish toxicity	LC50 mg/l	> 100	96 h			
	Acute algae toxicity	ErC50 mg/l	> 100	72 h			
	Acute crustacea toxicity		48 mg/l	48 h			
38668-48-3	1,1'-(p-Tolylimino)diprop	T					
	Acute fish toxicity	LC50	17 mg/l		Danio rerio (zebrafish)		
	Acute algae toxicity	ErC50	245 mg/l		Desmodesmus subspicatus		
	Acute crustacea toxicity	mg/l	28,8		Daphnia magna (Big water flea)		
	Algae toxicity	NOEC mg/l	57,8	72 d	Desmodesmus subspicatus		OECD 201
130-15-4	1,4-naphthoquinone						
	Acute fish toxicity	LC50 mg/l	0,045		Oryzias latipes (Ricefish)		
	Acute algae toxicity	ErC50 mg/l	0,42	72 h			
	·	EC50 mg/l	0,026	48 h			
	Algae toxicity	NOEC mg/l	0,07	3 d			

12.2. Persistence and degradability

The product has not been tested.



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 13 of 16

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
2082-81-7	Tetramethylene dimethacrylate			
	OECD 310	84 %	28	
25013-15-4	Vinyltoluene			
	OECD 310	36,7 %	28	
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
	OECD 301C	81%	28	
130-15-4	1,4-naphthoquinone			
		39 %	5	

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2082-81-7	Tetramethylene dimethacrylate	3,1
25013-15-4	Vinyltoluene	3,35
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	0,97
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate	4,91
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	2,17
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol	2,1
130-15-4	1,4-naphthoquinone	1,77

BCF

CAS No	Chemical name	BCF	Species	Source
25013-15-4	Vinyltoluene	100 - 320		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 14 of 16

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

14.4. Packing group:

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

14.4. Packing group:
Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 40, Entry 75





according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 15 of 16

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

Additional information

VOC content: 2,8 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level EC50: Effective concentration, 50%

ErC50: EC50 in terms of reduction of growth rate IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Acute Tox. 3: Acute toxicity, Category 3 Acute Tox. 2: Acute toxicity, Category 2 Acute Tox. 4: Acute toxicity, Category 4

Aquatic Acute 1: Acute aquatic hazard, Category 1
Aquatic Chronic 1: Long-term aquatic hazard, Category 1

Aquatic Chronic 3: Long-term aquatic hazard, Category 3

Asp. Tox. 1: Aspiration hazard, Category 1

Eye Dam. 1: Serious eye damage/eye irritation, Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2

Flam. Liq. 3: Flammable liquid, Category 3 Repr. 2: Reproductive toxicity, Category 2

Skin Corr. 1C: Skin corrosion/irritation, Category 1C



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. A

Revision date: 14.10.2022 Page 16 of 16

Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1A: Skin sensitilization, Category 1A Skin Sens. 1B: Skin sensitilization, Category 1B

STOT SE 3: Specific target organ toxicity (single exposure), Category 3

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

11000	
H226	Flammable liquid and vapour.
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)





according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. B

Revision date: 14.10.2022 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

FIRST300B / FIRST410B, Comp. B

UFI: S8XH-A835-YG0Y-AYD0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

compound mortar B-component (hardener)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: Scell-it

Street: 28 rue Paul Dubrule Place: F-59810 Lesquin

Telephone: +33(0) 320 329 818 Telefax: +33(0) 320 329 817

e-mail: technique@scellit.com
e-mail (Contact person): qualite@scellit.com
Internet: www.scellit.com

1.4. Emergency telephone Guy's St thomas' Poisons Unit, London: +44 870 243 2241

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Eye Irrit. 2; H319 Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Dibenzoyl peroxide

Signal word: Warning

Pictograms:



Hazard statements

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing vapours.

P280 Wear protective gloves and eye/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container to an approved waste disposal plant in accordance with

local/national regulation.



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. B

Revision date: 14.10.2022 Page 2 of 10

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No Index No REACH No			
	Classification (GB CLP Regulation)			
94-36-0	Dibenzoyl peroxide		5 - < 15 %	
	202-327-6	617-008-00-0	01-2119511472-50	
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H241 H319 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No Chemical name		
	Specific Conc	Limits, M-factors and ATE	
94-36-0	202-327-6	Dibenzoyl peroxide	5 - < 15 %
	oral: LD50 = 3 M chron.; H41	> 5000 mg/kg M acute; H400: M=10 0: M=10	

Further Information

The product has been tested for aquatic toxicity. The tests show no need for classification of the product as toxic and harmful to aquatic life. Test reports are available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media





according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. B

Revision date: 14.10.2022 Page 3 of 10

Suitable extinguishing media

Foam

Extinguishing powder

Water spray jet

Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protective equipment as required. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. B

Revision date: 14.10.2022 Page 4 of 10

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

Keep container tightly closed in a cool place.

storage temperature: 5 - 25°C

7.3. Specific end use(s)

see section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
94-36-0	Dibenzoyl peroxide			
Consumer DN	Consumer DNEL, long-term		systemic	2 mg/kg bw/day
Worker DNEL, long-term		dermal		13,3 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	39 mg/m³

PNEC values

CAS No	Substance	
Environment	Environmental compartment V	
94-36-0 Dibenzoyl peroxide		
Freshwater		0,00002 mg/l
Marine water		0,000002 mg/l
Freshwater sediment		0,013 mg/kg
Marine sediment 0		0,001 mg/kg

Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area





according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. B

Revision date: 14.10.2022 Page 5 of 10

must be ventilated by technical means.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Wear safety glasses.

Hand protection

Disposable gloves

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: > 0,2 mm

DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: solid (pasty)
Colour: black
Odour: characteristic

Odour: characteristic
Odour threshold: No data available

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

not determined
not determined

boiling range:

Flash point: not applicable

Flammability

Solid/liquid: not determined
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Self-ignition temperature

Solid:
Gas:

Decomposition temperature:

pH-Value:

Not determined

not determined

not determined

not determined

not determined

not determined

hereause the substance is known to be

because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. B

Revision date: 14.10.2022 Page 6 of 10

Vapour pressure: not determined

Density (at 20 °C): 1,59 g/cm³

Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties
Not oxidising.

Available oxygen content < 1%

no classification

Other safety characteristics

Solid content: not determined Evaporation rate: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

see section 10.3

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

Benzoic acid Benzene Biphenyl

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
94-36-0	Dibenzoyl peroxide				
	oral	LD50 > 5000 mg/kg	Rat		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Dibenzoyl peroxide)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. B

Revision date: 14.10.2022 Page 7 of 10

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

OECD 201 (Desmodesmus subspicatus)

IC10: (0 - 72 h) = 30 mg/lIC50: (0 - 72 h) = 150 mg/l

OECD 202 (Daphnia magna) EC0/NOEC (48h) = 100 mg/l (48h) = >500 mg/lEC50 (48h) = >>500 mg/lEC100

OECD 203 (Danio rerio)

LC0/NOEC (96 h): 250 mg/l				
LC50 (96 h) : > 500 mg/l				
LC100	(96 h)	: >> 500 mg/l		
No	Chemica	l name		

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
94-36-0	Dibenzoyl peroxide						
	Acute fish toxicity	LC50 mg/l	0,0602		Oncorhynchus mykiss (Rainbow trout)	OECD 203	
	Acute algae toxicity	ErC50 mg/l	0,0711		Pseudokirchneriella subcapitata	OECD 201	
	Acute crustacea toxicity	EC50 mg/l	0,11		Daphnia magna (Big water flea)	OECD 202	
	Algae toxicity	NOEC mg/l	0,02		Pseudokirchneriella subcapitata	OECD 201	
	Crustacea toxicity	NOEC mg/l	0,001		Daphnia magna (Big water flea)	OECD 211	
	Acute bacteria toxicity	(EC50	35 mg/l)	0,5 h		OECD 209	

12.2. Persistence and degradability

The product has not been tested.

	·			
CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
94-36-0	Dibenzoyl peroxide			
	OECD 301D	71%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.



according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. B

Revision date: 14.10.2022 Page 8 of 10

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
94-36-0	Dibenzoyl peroxide	3,2

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.No dangerous good in sense of this transport regulation.





according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. B

Revision date: 14.10.2022 Page 9 of 10

14.3. Transport hazard class(es):14.4. Packing group:No dangerous good in sense of this transport regulation.No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III) (SEVESO III):

Additional information

VOC content: 4,3 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level





according to UK REACH Regulation

FIRST300B / FIRST410B, Comp. B

Revision date: 14.10.2022 Page 10 of 10

EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

ICAO: International Civil Aviation Organization

IC50: Inhibitory concentration, 50%

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Acute 1: Acute aquatic hazard, Category 1 Aquatic Chronic 1: Long-term aquatic hazard, Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitilization, Category 1 Org. Perox. B: Organic Peroxides, Type B

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure	
Eye Irrit. 2; H319	Calculation method	
Skin Sens. 1; H317	Calculation method	

Relevant H and EUH statements (number and full text)

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)





according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

FIRST300G / FIRST410G, Comp. A

UFI: SRNH-68RV-PG00-U5PM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: Scell-it

Street: 28 rue Paul Dubrule Place: F-59810 Lesquin

Telephone: +33(0) 320 329 818 Telefax: +33(0) 320 329 817

e-mail: technique@scellit.com
e-mail (Contact person): qualite@scellit.com
Internet: www.scellit.com

1.4. Emergency telephone Guy's St thomas' Poisons Unit, London: +44 870 243 2241

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Sens. 1; H317 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Tetramethylene dimethacrylate;

Methacrylic acid, monoester with propane-1,2-diol;

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl]

(4-methylphenyl)amino]

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 2 of 16

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container to an approved waste disposal plant in accordance with

local/national regulation.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)				
2082-81-7	Tetramethylene dimethacrylate				
	218-218-1		01-2119967415-30		
	Skin Sens. 1B; H317				
25013-15-4	Vinyltoluene			1 - < 6 %	
	246-562-2		01-2119622074-50		
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Aquatic Acute 1, Aquatic Chronic 2; H226 H332 H315 H319 H400 H411				
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			< 2,5 %	
	248-666-3		01-2119490226-37		
	Eye Irrit. 2, Skin Sens. 1; H319 H317				
6846-50-0	1-Isopropyl-2,2-dimethyltrimeth	ylene Diisobutyrate		< 0,5 %	
	229-934-9		01-2119451093-47		
	Repr. 2, Aquatic Chronic 3; H361d H412				
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]				
	911-490-9		01-2119979579-10		
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H302 H315 H318 H317 H412				
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol			< 0,5 %	
	254-075-1		01-2119980937-17		
	Acute Tox. 2, Eye Irrit. 2, Aquatic Chronic 3; H300 H319 H412				
130-15-4	1,4-naphthoquinone			< 0,05 %	
	204-977-6		01-2120760462-57		
	Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H330 H301 H314 H318 H317 H335 H400 H410				

Full text of H and EUH statements: see section 16.



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 3 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
2082-81-7	218-218-1	Tetramethylene dimethacrylate	5 - < 15 %	
	dermal: LD50	dermal: LD50 = > 3000 mg/kg; oral: LD50 = 10066 mg/kg		
25013-15-4	246-562-2	Vinyltoluene	1 - < 6 %	
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 4585 mg/kg			
27813-02-1	248-666-3	Methacrylic acid, monoester with propane-1,2-diol	< 2,5 %	
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 2000 mg/kg			
6846-50-0	229-934-9	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate	< 0,5 %	
	dermal: LD50 = 18900 mg/kg; oral: LD50 = 3200 mg/kg			
	911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	< 0,5 %	
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 619 mg/kg			
38668-48-3	254-075-1	1,1'-(p-Tolylimino)dipropan-2-ol	< 0,5 %	
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 25 - < 200 mg/kg			
130-15-4	204-977-6	1,4-naphthoquinone	< 0,05 %	
		TE = 0,5 mg/l (vapours); inhalation: LC50 = 0,046 mg/l (dusts or mists); oral: LD50 M acute; H400: M=10 10: M=1		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eves

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam
Extinguishing powder
Water spray jet
Carbon dioxide (CO2)





according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 4 of 16

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic Carbon monoxide

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protective equipment as required. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not use for products which come into contact with the food stuffs.





according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 5 of 16

Further information on storage conditions

storage temperature: 5 - 25°C

7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 6 of 16

DNEL/DMEL values

CAS No Substance				
DNEL type	Exposure route	Effect	Value	
2082-81-7 Tetramethylene dimethacrylate				
Worker DNEL, long-term	inhalation	systemic	14,5 mg/m³	
Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	4,3 mg/m³	
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day	
25013-15-4 Vinyltoluene				
Worker DNEL, long-term	inhalation	systemic	37 mg/m³	
Worker DNEL, acute	inhalation	systemic	37 mg/m³	
Worker DNEL, long-term	inhalation	local	37 mg/m³	
27813-02-1 Methacrylic acid, monoester with propane-1,2-diol				
Worker DNEL, long-term	inhalation	systemic	14,7 mg/m³	
Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	8,8 mg/m³	
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day	
6846-50-0 1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate				
Worker DNEL, long-term	dermal	systemic	5 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	17,62 mg/m³	
Consumer DNEL, long-term	inhalation	systemic	4,35 mg/m³	
Consumer DNEL, long-term	oral	systemic	5 mg/kg bw/day	
Consumer DNEL, long-term	dermal	systemic	5 mg/kg bw/day	
- Reaction mass of 2,2'-[(4-methylphenyl)imino]bisether (4-methylphenyl)amino]	anol and Ethanol 2-[[2-(2-hydroxyethoxy)	ethyl]	
Worker DNEL, long-term	inhalation	systemic	9,8 mg/m³	
Worker DNEL, long-term	dermal	systemic	1,4 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	2,9 mg/m³	
Consumer DNEL, long-term	oral	systemic	0,83 mg/kg bw/day	
Consumer DNEL, long-term	dermal	systemic	0,83 mg/kg bw/day	
38668-48-3 1,1'-(p-Tolylimino)dipropan-2-ol				
Worker DNEL, long-term	inhalation	systemic	2 mg/m³	
Worker DNEL, long-term	dermal	systemic	0,6 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	0,3 mg/kg bw/day	
Consumer DNEL, long-term	dermal	systemic	0,3 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	0,4 mg/m³	
130-15-4 1,4-naphthoquinone				
Worker DNEL, long-term	inhalation	systemic	0,033 mg/m³	



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 7 of 16

PNEC values

CAS No Substance			
Environmental compartment	Value		
2082-81-7 Tetramethylene dimethacrylate			
Freshwater	0,043 mg/l		
Marine water	0,004 mg/l		
Freshwater sediment			
Freshwater sediment Marine sediment			
Micro-organisms in sewage treatment plants (STP)	2 mg/l		
Soil	0,573 mg/kg		
25013-15-4 Vinyltoluene			
Freshwater	0,05 mg/l		
Marine water	0,002 mg/l		
Freshwater sediment	0,684 mg/kg		
Marine sediment	0,684 mg/kg		
Soil	0,133 mg/kg		
27813-02-1 Methacrylic acid, monoester with propane-1,2-dic	l .		
Freshwater	0,904 mg/l		
Marine water	0,904 mg/l		
Freshwater sediment	6,28 mg/kg		
Marine sediment	6,28 mg/kg		
Micro-organisms in sewage treatment plants (STP)			
Soil	0,727 mg/kg		
6846-50-0 1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrat	te		
Freshwater	0,014 mg/l		
Marine water	0,001 mg/l		
Freshwater sediment	5,29 mg/kg		
Marine sediment	0,529 mg/kg		
Soil	1,05 mg/kg		
- Reaction mass of 2,2'-[(4-methylphenyl)imino]bis (4-methylphenyl)amino]	ethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl]		
Freshwater	0,048 mg/l		
Marine water	0,005 mg/l		
Freshwater sediment	0,12 mg/kg		
Marine sediment			
38668-48-3 1,1'-(p-Tolylimino)dipropan-2-ol			
Freshwater	0,017 mg/l		
Marine water			
Freshwater sediment 0,0783 n			
Marine sediment 0,0072 mg			
Soil	0,005 mg/kg		
130-15-4 1,4-naphthoquinone			
Freshwater 26,1 mg/l			
Marine water 2,61 mg/l			



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 8 of 16

Freshwater sediment	321 mg/kg
Marine sediment	32,1 mg/kg
Micro-organisms in sewage treatment plants (STP)	0,172 mg/l
Soil	49 mg/kg

Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Wear safety glasses.

Hand protection

Disposable gloves

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: > 0,2 mm

DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: solid (pasty)
Colour: light beige
Odour: characteristic
Odour threshold: No data available

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

not determined
not determined

boiling range:

Flash point: not applicable

Flammability

Solid/liquid: not determined



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 9 of 16

Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Self-ignition temperature

Solid: not determined Gas: not applicable Decomposition temperature: not determined pH-Value: not determined

Water solubility: The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 20 °C):

Relative vapour density:

not determined

1,72 g/cm³

not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties Not oxidising.

Other safety characteristics

Solid content: not determined Evaporation rate: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Response: Oxidising agent, strong

10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 11282,6 mg/kg; ATE (inhalation vapour) 265,95 mg/l; ATE (inhalation dust/mist) 36,266 mg/l



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 10 of 16

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
2082-81-7	Tetramethylene dimethacrylate					
	oral	LD50 10 mg/kg	0066	Rat		
	dermal	LD50 > mg/kg	3000	Rabbit		
25013-15-4	Vinyltoluene					
	dermal	LD50 45 mg/kg	585	Rabbit		
	inhalation vapour		1 mg/l			
	inhalation dust/mist	ATE 1,	,5 mg/l			
27813-02-1	Methacrylic acid, mon	oester with pro	pane-1,	2-diol		
	oral	LD50 > mg/kg	2000	Rat		
	dermal	LD50 > mg/kg	5000	Rabbit		
6846-50-0	1-Isopropyl-2,2-dimetl	nyltrimethylene	Diisobu	tyrate		
	oral	LD50 32 mg/kg	200	Rat		
	dermal	LD50 18 mg/kg	8900	Guinea pig		
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]					
	oral	LD50 61 mg/kg	19	Rat		
	dermal	LD50 > mg/kg	2000	Rat		
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol					
	oral	LD50 > 200 mg/kg	25 - <	Rat		
	dermal	LD50 > mg/kg	2000	Rat		
130-15-4	1,4-naphthoquinone					
	oral	LD50 12 mg/kg	24	Rat		
	inhalation vapour	ATE 0,	,5 mg/l			
	inhalation (4 h) dust/mist	LC50 0, mg/l	,046	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Tetramethylene dimethacrylate; Methacrylic acid, monoester with propane-1,2-diol; Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]; 1,4-naphthoquinone)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.





according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 11 of 16

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 12 of 16

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
2082-81-7	Tetramethylene dimetha	acrylate						
	Acute algae toxicity	ErC50 mg/l	9,79	72 h				
	Crustacea toxicity	NOEC mg/l	5,09	21 d				
25013-15-4	Vinyltoluene							
	Acute fish toxicity	LC50 mg/l	1 - 10	96 h				
	Acute algae toxicity	ErC50 mg/l	0,319	72 h				
	Acute crustacea toxicity	EC50	9,3 mg/l	48 h	Daphnia magna (Big water flea)			
27813-02-1	Methacrylic acid, monoe	ester with p	propane-1,2	2-diol				
	Acute algae toxicity	ErC50 mg/l	> 97,2	72 h	Pseudokirchneriella subcapitata			
	Acute crustacea toxicity	EC50 mg/l	> 143	48 h	Daphnia magna (Big water flea)			
	Algae toxicity	NOEC	mg/l					
6846-50-0	1-Isopropyl-2,2-dimethy	Itrimethyle	ne Diisobut	yrate				
	Algae toxicity	NOEC mg/l	2,25	3 d				
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]							
	Acute fish toxicity	LC50 mg/l	> 100	96 h				
	Acute algae toxicity	ErC50 mg/l	> 100	72 h				
	Acute crustacea toxicity		48 mg/l	48 h				
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol							
	Acute fish toxicity	LC50	17 mg/l		Danio rerio (zebrafish)			
	Acute algae toxicity	ErC50	245 mg/l		Desmodesmus subspicatus			
	Acute crustacea toxicity	mg/l	28,8		Daphnia magna (Big water flea)			
	Algae toxicity	NOEC mg/l	57,8	72 d	Desmodesmus subspicatus		OECD 201	
130-15-4	1,4-naphthoquinone							
	Acute fish toxicity	LC50 mg/l	0,045		Oryzias latipes (Ricefish)			
	Acute algae toxicity	ErC50 mg/l	0,42	72 h				
	·	EC50 mg/l	0,026	48 h				
	Algae toxicity	NOEC mg/l	0,07	3 d				

12.2. Persistence and degradability

The product has not been tested.



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 13 of 16

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
2082-81-7	Tetramethylene dimethacrylate					
	OECD 310	84 %	28			
25013-15-4	Vinyltoluene					
	OECD 310	36,7 %	28			
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol					
	OECD 301C	81%	28			
130-15-4	1,4-naphthoquinone					
		39 %	5			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2082-81-7	Tetramethylene dimethacrylate	3,1
25013-15-4	Vinyltoluene	3,35
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	0,97
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate	4,91
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	2,17
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol	2,1
130-15-4	1,4-naphthoquinone	1,77

BCF

CAS No	Chemical name	BCF	Species	Source
25013-15-4	Vinyltoluene	100 - 320		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 14 of 16

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

14.4. Packing group:

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

14.4. Packing group:
Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 40, Entry 75





according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 15 of 16

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

Additional information

VOC content: 2,8 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level EC50: Effective concentration, 50%

ErC50: EC50 in terms of reduction of growth rate IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Acute Tox. 3: Acute toxicity, Category 3 Acute Tox. 2: Acute toxicity, Category 2 Acute Tox. 4: Acute toxicity, Category 4

Aquatic Acute 1: Acute aquatic hazard, Category 1
Aquatic Chronic 1: Long-term aquatic hazard, Category 1

Aquatic Chronic 3: Long-term aquatic hazard, Category 3

Asp. Tox. 1: Aspiration hazard, Category 1

Eye Dam. 1: Serious eye damage/eye irritation, Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2

Flam. Liq. 3: Flammable liquid, Category 3 Repr. 2: Reproductive toxicity, Category 2

Skin Corr. 1C: Skin corrosion/irritation, Category 1C



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. A

Revision date: 14.10.2022 Page 16 of 16

Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1A: Skin sensitilization, Category 1A Skin Sens. 1B: Skin sensitilization, Category 1B

STOT SE 3: Specific target organ toxicity (single exposure), Category 3

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure				
Skin Sens. 1; H317	Calculation method				
Aquatic Chronic 3; H412	Calculation method				

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)





according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. B

Revision date: 14.10.2022 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

FIRST300G / FIRST410G, Comp. B

UFI: 0CPH-R8KN-TG0F-FJS2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

compound mortar B-component (hardener)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: Scell-it

Street: 28 rue Paul Dubrule Place: F-59810 Lesquin

Telephone: +33(0) 320 329 818 Telefax: +33(0) 320 329 817

e-mail: technique@scellit.com
e-mail (Contact person): qualite@scellit.com
Internet: www.scellit.com

1.4. Emergency telephone Guy's St thomas' Poisons Unit, London: +44 870 243 2241

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Eye Irrit. 2; H319 Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Dibenzoyl peroxide

Signal word: Warning

Pictograms:



Hazard statements

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing vapours.

P280 Wear protective gloves and eye/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container to an approved waste disposal plant in accordance with

local/national regulation.



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. B

Revision date: 14.10.2022 Page 2 of 10

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name					
	EC No Index No REACH No					
	Classification (GB CLP Regulation)					
94-36-0	Dibenzoyl peroxide					
	202-327-6	617-008-00-0	01-2119511472-50			
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H241 H319 H317 H400 H410					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc.	Limits, M-factors and ATE		
94-36-0	202-327-6	Dibenzoyl peroxide	5 - < 15 %	
	oral: LD50 = > 5000 mg/kg M acute; H400: M=10 M chron.; H410: M=10			

Further Information

The product has been tested for aquatic toxicity. The tests show no need for classification of the product as toxic and harmful to aquatic life. Test reports are available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media





according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. B

Revision date: 14.10.2022 Page 3 of 10

Suitable extinguishing media

Foam

Extinguishing powder

Water spray jet

Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protective equipment as required. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. B

Revision date: 14.10.2022 Page 4 of 10

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

Keep container tightly closed in a cool place.

storage temperature: 5 - 25°C

7.3. Specific end use(s)

see section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
94-36-0	Dibenzoyl peroxide						
Consumer DN	Consumer DNEL, long-term		systemic	2 mg/kg bw/day			
Worker DNEL, long-term		dermal		13,3 mg/kg bw/day			
Worker DNEL, long-term		inhalation	systemic	39 mg/m³			

PNEC values

CAS No	Substance			
Environmental compartment Value				
94-36-0	Dibenzoyl peroxide			
Freshwater	Freshwater 0,00002 mg/l			
Marine water	0,000002 mg/l			
Freshwater sediment		0,013 mg/kg		
Marine sediment		0,001 mg/kg		

Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area





according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. B

Revision date: 14.10.2022 Page 5 of 10

must be ventilated by technical means.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Wear safety glasses.

Hand protection

Disposable gloves

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: > 0,2 mm

DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: solid (pasty)
Colour: black
Odour: characteristic

Odour: characteristic
Odour threshold: No data available

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

not determined
not determined

boiling range:

Flash point: not applicable

Flammability

Solid/liquid: not determined
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Self-ignition temperature

Solid:
Gas:

Decomposition temperature:
pH-Value:

Not determined
not determined
not determined
not determined
The study does not need to be conducted
because the substance is known to be

because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. B

Revision date: 14.10.2022 Page 6 of 10

Vapour pressure: not determined

Density (at 20 °C): 1,59 g/cm³

Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties

Not oxidising.

Available oxygen content < 1%

no classification

Other safety characteristics

Solid content: not determined Evaporation rate: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

see section 10.3

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

Benzoic acid Benzene Biphenyl

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name								
	Exposure route Dose Species Source Method								
94-36-0	Dibenzoyl peroxide								
		LD50 > 5 mg/kg	5000	Rat					

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Dibenzoyl peroxide)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. B

Revision date: 14.10.2022 Page 7 of 10

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

OECD 201 (Desmodesmus subspicatus)

IC10: (0 - 72 h) = 30 mg/lIC50: (0 - 72 h) = 150 mg/l

OECD 202 (Daphnia magna) EC0/NOEC (48h) = 100 mg/l (48h) = >500 mg/lEC50 EC100 (48h) = >>500 mg/l

OECD 203 (Danio rerio) : > 500 mg/l

LC0/NOEC (96 h): 250 mg/l LC50 (96 h) LC100 (96 h) : >> 500 mg/l

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
94-36-0	Dibenzoyl peroxide							
	Acute fish toxicity	LC50 mg/l	0,0602		Oncorhynchus mykiss (Rainbow trout)	OECD 203		
	Acute algae toxicity	ErC50 mg/l	0,0711		Pseudokirchneriella subcapitata	OECD 201		
	Acute crustacea toxicity	EC50 mg/l	0,11		Daphnia magna (Big water flea)	OECD 202		
	Algae toxicity	NOEC mg/l	0,02		Pseudokirchneriella subcapitata	OECD 201		
	Crustacea toxicity	NOEC mg/l	0,001		Daphnia magna (Big water flea)	OECD 211		
	Acute bacteria toxicity	(EC50	35 mg/l)	0,5 h		OECD 209		

12.2. Persistence and degradability

The product has not been tested.

	·			
CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
94-36-0	Dibenzoyl peroxide			
	OECD 301D	71%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.



according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. B

Revision date: 14.10.2022 Page 8 of 10

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
94-36-0	Dibenzoyl peroxide	3,2

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number: 14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.
No dangerous good in sense of this transport regulation.





according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. B

Revision date: 14.10.2022 Page 9 of 10

14.3. Transport hazard class(es): 14.4. Packing group:No dangerous good in sense of this transport regulation.
No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

Additional information

VOC content: 4,3 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level





according to UK REACH Regulation

FIRST300G / FIRST410G, Comp. B

Revision date: 14.10.2022 Page 10 of 10

EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

ICAO: International Civil Aviation Organization

IC50: Inhibitory concentration, 50%

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Acute 1: Acute aquatic hazard, Category 1 Aquatic Chronic 1: Long-term aquatic hazard, Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitilization, Category 1 Org. Perox. B: Organic Peroxides, Type B

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure	
Eye Irrit. 2; H319	Calculation method	
Skin Sens. 1; H317	Calculation method	

Relevant H and EUH statements (number and full text)

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)